

# Total Solutions System **STATIONARY BATTERIES**

# WINNER<sup>®</sup>

BATTERY  
SWITCH FOR SUCCESS

## AGM FRONT TERMINAL

- Stand by front access 12V AGM rechargeable monoblocks
- Low resistance microporous glass fibre separators
- Centralized gas venting system.
- 19" & 23" footprint for easy racks/cabinets installation & service
- Advanced solution for high discharge performance
- Design service life is 12 years at 25°C



[www.winnerbattery.net](http://www.winnerbattery.net)

# MARS


HIGH INTEGRITY VALVE REGULATED LEAD ACID SERIES



Type No	Voltage	Capacity	Dimensions (mm)				Layout	Terminal	Weight (Kg)
	V	AH (C10)	L	W	H	T.H.			
100-12A	12	100	558	125	230	230	4	FT2	38,00
125-12A	12	125	558	125	270	270	4	FT2	45,20
150-12A	12	150	558	125	310	310	4	FT2	54,50
175-12A	12	175	558	125	310	310	4	FT2	55,00
55-12B	12	55	277	106	222	222	4	F14	17,20
80-12B	12	80	394	110	288	288	4	F18	27,50
95-12B	12	95	394	105	270	270	4	FT1	28,50
100-12B	12	100	394	110	288	288	4	F18	34,50
105-12B	12	105	508	110	238	238	4	F15	35,40
125-12B	12	125	550	110	288	288	4	F17.1	39,50
150-12B	12	150	550	110	288	288	4	F17.1	48,30
165-12B	12	165	550	110	288	288	4	F17.1	49,00

More types available on request

#### KEY FOR LAY OUT



#### APPLICATIONS

Telecommunication Back Up Systems  
 U.P.S / E.P.S  
 Switchgear Control Power  
 Emergency Lighting Systems  
 Renewable Energy Plant Data Centers  
 Radio & Broadcasting Systems

#### STANDARDS

- IEC60896-21/22 2004
- IEC 61056-1/2 2002
- BS 6290-4 1999
- Eurobat Guide -12 years and longer "long life"



Version: 2013/05

Wherever batteries go



VIOSY S.A. • Central Office:  
 17th klm N.R. Athens-Corinth, 19300, Aspropyrgos, Athens, Greece • Tel.: +30 210 3474444 • Fax: +30 210 3479931  
<http://www.winnerbattery.net> • e-mail: [info@winnerbattery.net](mailto:info@winnerbattery.net) • <http://www.viosy.gr> • e-mail: [info@viosy.gr](mailto:info@viosy.gr)