



# ENERGON DYNAMIC 10W40

- ▣ **AVAILABLE FOR:** ALL GASOLINE, LPG & DIESEL ENGINES WITH OR WITHOUT TURBO CHARGE
- ▣ **TECHNICAL PRESCRIPTIONS:** API: SL/CF, ACEA A3/B4, MB 229.1, VW. 500/505 , PORSCHE, EFEI SEQ VI-API SH
- ▣ **AVAILABLE PACKAGES:**

PACKAGES		
	PIECES	Lt
A.	12	1
B.	4	5
C.	1	205



# PROTON POWER 15W40

- **FOR 4 – STROKE DIESEL ENGINES ON&OFF ROAD**
- **TECHNICAL PRESCRIPTIONS:** ACEA E9/E7, API SJ4,  
MB 228.31, MAN (M3275), VOLVO VDS-4, CAT ECF
- **AVAILABLE PACKAGES:**

## PACKAGES

	PIECES	Lt
<b>A.</b>	12	1
<b>B.</b>	4	5
<b>C.</b>	1	20
<b>D.</b>	1	205

# PROTON POWER 20W50

- ▣ **FOR HEAVY DUTY DIESEL ENGINES.**
- ▣ **TECHNICAL PRESCRIPTIONS:** ACEA B4 / B3 / E3,  
API CH – 4 / CG – 4 / CF / CE / SJ, MB 228.3,  
MAN (M 3275), VOLVO VDS – 2, KHD
- ▣ **AVAILABLE PACKAGES :**

<b>PACKAGES</b>		
	<b>PIECES</b>	<b>Lt</b>
<b>A.</b>	1	20
<b>B.</b>	1	205





# DROMON PLUS 80W90

- ▣ LUBRICATION OF HEAVY CHARGED TRANSMISSIONS THAT REQUIRE SPECIAL ANTI-WEAR PROTECTION.
- ▣ TECHNICAL PRESCRIPTIONS: AGI GL – 5, MIL - L – 2105D
- ▣ AVAILABLE PACKAGES:

PACKAGE		
	PIECES	Lt
A.	4	5
B.	1	20
C.	1	205

# **DROMON PLUS 75W90**

- ▣ **FOR ALL HEAVY CHARGED GEAR SYSTEMS WORKING UNDER VERY LOW TEMPERATURES AND REQUIRING SPECIAL ANTI-WEAR PROTECTION.**
  
- ▣ **TECHNICAL PRESCRIPTIONS:**
  
- ▣ **API: GL - 5,    MIL – L – 2105 D**



# AXION COOL 50 / 50

▣ **ANTIFREEZE COOLANT FOR ALL YEAR ROUND, FOR VERY GOOD COOLING OF GAS, LPG AND DIESEL ENGINES WITH OPEN OR CLOSED COOLING SYSTEM.**

▣ **TECHNICAL PRESCRIPTIONS:** BS-6580, AFNOR: 15601,  
ASTM:D-3306&D-4656 CUNA: NC-956-16, O NORM,  
SAE:J1034, COLOUR: BLUE

▣ **AVAILABLE PACKAGES:**

<b>PACKAGE</b>		
	<b>PIECES</b>	<b>Lt</b>
<b>A.</b>	12	1
<b>B.</b>	4	5
<b>C.</b>	1	205
<b>D.</b>	1	1000



Wherever batteries go



**WINNER LUBRICANTS – TOTAL SOLUTIONS SYSTEM**

# **AXION COOL 100**

- ▣ **ANTIFREEZE PERMANENT FOR ALL YEAR ROUND.**
- ▣ **FOR ALL ENGINE COOLING SYSTEM OF ALUMINUM OR FERROUS CONSTRUCTION.**
- ▣ **RECOMMENDED FOR EXCELLENT PROTECTION AGAINST FROST, OVERHEATING AND CORROSION.**
- ▣ **TECHNICAL PRESCRIPTIONS: BS – 6580, ASTM: D 3306,**

**SAE: J 1034, AFNOR : NF – R 15 – 601, COLOUR: YELLOW**